

# PP Blend Adsorbent Media



## Basic Information:

PP Blend adsorbent media is a 50/50 percent blend of PureAir 8 potassium permanganate-based media and Sulphasorb 2™ acid gas removal media specifically designed for the removal of corrosive gases commonly found in the Pulp and Paper and Petrochemical and Refinery industries.

**Note: PP Blend media meets the requirements for UL certification.**



General Description	Product Specifications	Removal Capacity
<p>PP Blend has the combined properties and benefits of PureAir 8 and Sulphasorb 2™.</p> <p><b>PureAir 8:</b> Spherical porous pellets formed from a combination of powdered activated alumina and other binders, suitably impregnated with potassium permanganate to provide optimum adsorption, absorption, and oxidation of a wide variety of gaseous contaminants.</p> <p><b>PureAir Sulphasorb 2™:</b> Porous, cylindrical pellets of high grade bituminous activated carbon.</p>	<ul style="list-style-type: none"> <li>• Particle Size: See base products</li> <li>• Density: 735 kg/m<sup>3</sup> (46 lbs/ft<sup>3</sup>)</li> <li>• Surface Area: See base products</li> <li>• Typical Moisture Content %: See base products</li> <li>• Crush Test: See base products</li> <li>• Abrasion Loss %: See base products</li> <li>• Relative Pressure Drop: See Curve B</li> <li>• Permanganate Content: See base products</li> <li>• CTC Value: See base products</li> <li>• Iodine #: See base products</li> </ul>	<ul style="list-style-type: none"> <li>• Hydrogen Sulfide: 19.0% by weight</li> <li>• Sulfur Dioxide: 7.0% by weight</li> <li>• Nitric Oxide: 2.5% by weight</li> <li>• Nitrogen Dioxide: 14.95% by weight</li> <li>• Formaldehyde: 1.5% by weight</li> <li>• Chlorine: 5.9% by weight</li> </ul>

+1 678.935.1431

Toll Free: 866.543.7479

[www.PureAirFiltration.com](http://www.PureAirFiltration.com)

6050 Peachtree Pkwy Suite 240-187. Norcross, GA 30092 USA

