

Carbsorb Adsorbent Media



Basic Information:

- PureAir Carbsorb targets gases, specifically hydrogen sulfide.
- PureAir starts with the highest grade activated carbon and activated alumina ensuring the greatest possible adsorption capacity is reached. The carbon and alumina are impregnated with a proprietary caustic compound to neutralize acid gases.
- This product is designed to perform exceptionally well in both PureAir and other manufacturers systems.



General Description	Product Specifications	Removal Capability
<ul style="list-style-type: none"> • Porous, spherical or cylindrical pellets of high grade activated carbon and activated alumina • Available in the following varieties: SH, KH, and CO • All varieties are UL compliant. 	<ul style="list-style-type: none"> • Particle Size: 4mm • Density: 690 kg/m³ (43 lbs/ft³) • Surface Area: 350 m²/g • Typical Moisture Content %: 15% • Crush Test: 35 lbs - 70 lbs • Abrasion Loss %: 4% • Relative Pressure Drop: See Curve B* • CTC Value: 70% • Butane Activity: 27% minimum <p>*See Curves Details at pureairfiltration.com/curves/</p>	<ul style="list-style-type: none"> • Hydrogen Sulfide - 26% by weight • Sulfur Dioxide - 10% by weight • Chlorine - 10% by weight • Dichloride - 14% by weight

+1 678.935.1431

Toll Free: 866.543.7479

www.PureAirFiltration.com

6050 Peachtree Pkwy, Suite 240-187, Atlanta, GA 30092 U.S.A.

