

Packaged Filter Unit (PFU)

The Packaged Filter Units (PFU) filter air in controlled environments, like control rooms and data centers, to protect computer equipment and electronics from corrosion. The standard PFU is available in three stationary models (PFU- 1000, 2000, and 3000) and two portable units (PFU-Mini and PFU-Mobile) designed to fit into tight space restrictions and plug into standard electrical sockets.

As the air passes through PureAir's chemisorbant media, harmful corrosive gases are captured and permanently removed. Purified air is sent out the top of the unit where it is used to cool servers without harming electrical components while also improving air quality.

PureAir can custom design a corrosion management solution to remove corrosive gases and prevent both hardware and server failure. PureAir's equipment combined with its high-quality chemisorbant media can remove more than 99% of gases that could harm electronic equipment resulting in costly repairs, downtime events, and possible data loss.

Key Benefits

- Compact, powerful, and portable
- Self-contained, vertical system
- Improve Indoor Air Quality
- Protect electronics from corrosion
- Prevent data loss



Model	Media Capacity	Electrical Requirements	Max Airflow CMH (CFM)	Room Sizing by Model and Air Quality Level*		
				G2	G3	GX
PFU-Mini (Mobile, Plug In, On Casters, (8) 18" Plastic Cylinders)	0.037 m ³ (1.3 ft ³)	120 V/60 Hz Standard 230 V/50 Hz Optional	850 (500)	600 m ³ (20,000 ft ³)	300 m ³ (10,000 ft ³)	150 m ³ (5,000 ft ³)
PFU-Mobile (Mobile, Plug In, On Casters, (16) 24" Plastic Cylinders)	0.1 m ³ (3.52 ft ³)	120 V/60 Hz Standard 230 V/50 Hz Optional	1,700 (1,000)	1,200 m ³ (40,000 ft ³)	600 m ³ (20,000 ft ³)	300 m ³ (10,000 ft ³)
PFU-1000 (Stationary, Hardwired, (4) PP12 Module Sets)	0.11 m ³ (4 ft ³)	460 V 3 ph, 60 Hz	1,700 (1,000)	1,200 m ³ (40,000 ft ³)	600 m ³ (20,000 ft ³)	300 m ³ (10,000 ft ³)
PFU-2000 (Stationary, Hardwired, (8) PP12 Module Sets)	0.22 m ³ (8 ft ³)	460 V 3 ph, 60 Hz	3,400 (2,000)	2,400 m ³ (85,000 ft ³)	1,200 m ³ (40,000 ft ³)	600 m ³ (20,000 ft ³)
PFU-3000 (Stationary, Hardwired, (12) PP12 Module Sets)	0.34 m ³ (12 ft ³)	460 V 3 ph, 60 Hz	5,100 (3,000)	3,600 m ³ (127,000 ft ³)	1,800 m ³ (64,000 ft ³)	900 m ³ (32,000 ft ³)



BENEFITS	FEATURES
Powerful and Compact	- Vertical, stand-alone airflow system - Minimal noise 850 - 5,100 CMH (500 - 3,000 CFM)
Highest Filtration Efficiency	- Positive seal to prevent air bypass and ensure removal of unwanted gas molecules - Low EMF brushless AC blower motor - Integral particulate filters
Quick Access, Low Maintenance	- Door opens for easy access to internal parts and media for maintenance and changeout - Low energy consumption - Differential pressure gauges indicate filter changes
Customizable	- Multiple sizes, configurations, and optional features - Can produce pressurization, recirculation, or both - Multiple options for media passes
Multiple Applications	- Protect critical electronics and IT equipment - Prevent data loss - Improve air quality - Commercial and industrial odor control

The PFU Units are available in this standard configuration:

Protecting Critical Electronics
MERV 8 (G4) Dust Prefilter
PureAir chemisorbant media filled in low pressure drop disposable module
MERV 14 (F7) Dust Final Filter



Notable Customers

- Barclays Bank*
- Data Clean Asia*
- Farmers Insurance*
- GETCO*
- Google*
- Hewlett-Packard*
- HSCB Bank*
- Innodata*
- Intel*
- Turner Broadcasting Systems*